



A POLI-TAPE GROUP Company

DIGIT One Way Vision

Product Information

One Way Vision Vinyl (white gloss, 160 µ) with clear solvent based acrylic adhesive (permanent), laminated on a two-sided PE-coated silicone paper liner (140 g/m²).

The PVC offers a high dimensional stability and is suitable for applications on flat glass surface.

Especially designed for decoration of car windows, public vehicles windows and shop windows showing the printed surface outside but allowing a good see-through from the inside.

Designed to be highly resistant to solvent ink aggression during printing process and to guarantee very good printing performance on any solvent and eco-solvent based ink-jet printer.

Once applied on glass, it can be removed without leaving adhesive residues.

Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

Technical Data

Carrier:	Monomeric PVC, highly stabilized, calendared
Thickness:	160 µ +/- 5 %
Holes diameter:	1,6 mm +/- 0,1 %
Adhesive:	clear solvent acrylic, removable
Adhesion:	2,5 N/cm
Liner:	two-sided PE-coated silicone paper (140 g/m ²)
Application temperature:	+10 - +40 °C
Temperature durability :	- 40 - +80 °C
Outdoor durability:	1 year (unprinted film)

Standard Dimensions

1370 mm x 50 m
1520 mm x 50 m

KEMICA S.r.l.

Via F.lli Rusjan, 76 - Frazione Rupa
34070 Savogna d'Isonzo (GO) - ITALIA

Phone: +39 0481 882 501
Fax: +39 0481 882 440

E-Mail: info@kemicasrl.it
Internet: www.kemica.it

12/09/2016

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.