

TECHNICAL REPORT

LAC 920



M2/B1/BS

APPLICATIONS

- storage shelters
- Hangar covers

PRODUCT INFORMATION

WIDTH	300 cm
WEIGHT	900 g/m ²
BASE CLOTH	high tenacity polyester 1100 dTex
COATING	PVC coating, system LOWICK ® Protection Anti UV and Fungicide
FINISH	CLEANGARD ® lacquer both sides
COLOUR	White – other colours on special production

PRODUCT CHARACTERISTICS

TENSILE STRENGTH	400/380 daN	NF EN ISO 1421
TEAR STRENGTH	60/50 daN	DIN 53363
ADHESION	10 daN / 5 cm	NF EN ISO 2411
TEMPERATURE STABILITY:		
in ° Celsius	- 30°C to + 70°C	NF EN 1876-2
in ° Fahrenheit	- 22°F to +158°F	Test during 24 hours
Flame Retardancy	M2/B1/BS NFPA 701 / B-s2-d0	

Average values +/- 10 % non contractual



415 avenue de Savoie – SAINT-CLAIR-DE-LA-TOUR – 38357 La tour du Pin
France

Tél. 33 (0)4 74 83 51 00 – Fax 33 (0)4 74 83 51 01

www.dickson-coatings.com

Date : 09/2012